

Mseries

Robust. Reliable. And ready for the job.



**WACKER
NEUSON**
all it takes!

Vibratory Plates

MP15

These Wacker Neuson vibratory plate offers functionality and performance at a real value price. The compact design allows for compaction of mixed soils in the narrowest of spaces even in extremely narrow trenches. The guide handle with vibration damping means longer working hours and less fatigue for the operator.



MP15



Low hand-arm-vibrations.

Cyclonic 3 stage air-filtration system.

Ergonomically designed lifting handles make loading and unloading from transport vehicles easier for the operator.

Tough ductile iron baseplate is extremely durable even under extreme conditions and provides long service life.

SPECIFICATOINS	UNIT	MP15-CE
Dry weight	kg	83
Size of base plate (w x l)	mm	500 x 588
Centrifugal force	kN	15
Max. forward travel	m/min	20
Max. compacted area	m ² /h	600
Max. gradeability (depending on soil)	%	30
Water tank capacity	l	8.3
Engine model		Loncin-G210F
Engine type		Air-cooled, single cylinder, 4-cycle gasoline engine
Engine displacement	cm ³	212
Engine rated power	kW/3600 rpm	4.4
Fuel consumption	l/h	1.0
Fuel tank capacity	l	3.6

www.wackerneuson.com/m